MATERIAL SPECIFICATION		
Arconic-Köfém Mill Products Hungary Llc.		
I.D. No.:	Magnesium	
O-SPEC-52-EURAMG100ING	SPECIFICATION	
Date: 2003.02.19.		ARCONIC
Modification: 8/07.11.2023		
Prepared by: Berki Csaba	Approved by: Szántó Ró	bert
Checked by: Szalai Viktor		

### 1. Item: EURAMG100ING

### 2. Chemical composition:

Product supplied under the terms of this specification shall conform to the following chemical composition limits:

	Min. (%)	Max. (%)
Mg	99,9	
Other e	elements	Max. (%)
Si		0,02
Fe		0,03
Cu		0,01
Mn		0,03
Na		0,01



### 3. Physical characteristics:

Surface of Mg ingots weighing 7-8 KGs should be metallic, shiny, free of oxidation, protective coatings and surface wetness which would cause metal explosion when getting into molten metal. MG metal should be free of any kind of physical contaminations having negative effect on the composition or structure of finished goods (oil, oilmud, dust).

# 4. Packaging and delivery:

## 4.1. Material and shape of pallet:

The material of the pallets shall be exclusively magnesium metal and shall be equal to the chemical composition of the ingots. Size and form of magnesium pallets should be designed to enable the pallets to be moved by fork lift trucks by all the four sides, allowing a space of a minimum of 100 mm for the truck's fork at the bottom of the pallets.

### 4.2. Weight and size of magnesium lot:

Weight and size of magnesium lot is defined by the physical parameters of pre-heating furnaces. One individual lot shall weigh maximum 1 MT, with the size of 900x900x1000 mm.

O-SPEC-52-EURAMG100ING         SP           Date: 2003.02.19.         Modification: 8/07.11.2023         Prepared by: Berki Csaba           Checked by: Szalai Viktor         4.3. Striping, fixing and packaging:         .           Ingots shall be stacked by stee avoid the lot falling apart.         .         Foil sack as covering material s be placed under the sack to marge in the sack to marge in the sack of the sack to marge in the sack of the sack to marge in the sack to the sack to marge	hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>I.D. No.:</li> <li>O-SPEC-52-EURAMG100ING</li> <li>Date: 2003.02.19.</li> <li>Modification: 8/07.11.2023</li> <li>Prepared by: Berki Csaba</li> <li>Checked by: Szalai Viktor</li> <li>4.3. Striping, fixing and packaging: <ul> <li>Ingots shall be stacked by stee avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to mamelting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> </ul> </li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>Application of the pallet (accord end to be delivered by normal to be supplied by: <ul> <li>Producer's certificate of analysis per each side.</li> </ul> </li> <li>5. Accompanying documents: <ul> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis per each side.</li> <li>Safety Data Sheet, only with first de shipping document</li> <li>Packing list</li> <li>ISO 9001 certificate (only with first de shipping document</li> <li>One of the documents must contair uname</li> </ul> </li> </ul>	Approved by: Szántó R stripes. 3 stripes per sic hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood si	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
Date: 2003.02.19.         Modification: 8/07.11.2023         Prepared by: Berki Csaba         Checked by: Szalai Viktor         4.3. Striping, fixing and packaging:         -         Ingots shall be stacked by stee avoid the lot falling apart.         -       Foil sack as covering material s be placed under the sack to ma melting.         -       Application of textile hoods is ne from damages during transport plastic stripes per each side.         4.4. Marking (on two sides, giving the info - name of producer (name of smelte - name of goods (Mg metal)         - net weight (in KGs)         - serial number of the pallet (accord 4.5. Delivery         - Pallets to be delivered by normal to safety Data Sheet: only with first de Shipping document         - Safety Data Sheet: only with first de Shipping document         - Packing list.         - ISO 9001 certificate (only with fir qualification)         - One of the documents must contair - Item name	Approved by: Szántó R stripes. 3 stripes per sic nould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood si	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>Modification: 8/07.11.2023</li> <li>Prepared by: Berki Csaba</li> <li>Checked by: Szalai Viktor</li> <li>4.3. Striping, fixing and packaging: <ul> <li>Ingots shall be stacked by stee avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to ma melting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> </ul> </li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>4.5. Delivery <ul> <li>Pallets to be delivered by normal to be delivered by normal to be delivered by normal to be supplied by:</li> <li>Producer's certificate of analysis per each side.</li> </ul> </li> <li>5. Accompanying documents: <ul> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis per each side.</li> <li>Shipping document</li> <li>Packing list.</li> <li>ISO 9001 certificate (only with first de shipping document provide the documents must contair response)</li> </ul> </li> </ul>	stripes. 3 stripes per sid hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>Prepared by: Berki Csaba</li> <li>Checked by: Szalai Viktor</li> <li>4.3. Striping, fixing and packaging: <ul> <li>Ingots shall be stacked by stee avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to mamelting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> </ul> </li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the inform damages during transport plastic stripes per each side.</li> <li>4.5. Delivery <ul> <li>Pallets to be delivered by normal to be delivered by normal to be supplied by:</li> <li>Producer's certificate of analysis per each side.</li> </ul> </li> <li>5. Accompanying documents: <ul> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis per each side.</li> <li>Shipping document</li> <li>Packing list</li> <li>ISO 9001 certificate (only with fir qualification)</li> <li>One of the documents must contair rest in the name</li> </ul> </li> </ul>	stripes. 3 stripes per sid hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>Checked by: Szalai Viktor</li> <li>4.3. Striping, fixing and packaging:         <ul> <li>Ingots shall be stacked by stee avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to mamelting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> </ul> </li> <li>4.4. Marking (on two sides, giving the informed amages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the informed amages during transport plastic stripes per each side.</li> <li>1. name of producer (name of smelter aname of goods (Mg metal)             <ul> <li>net weight (in KGs)</li> <li>serial number of the pallet (accord the pallets to be delivered by normal the supplied by:</li> <li>Pallets to be delivered by normal the stript of analysis per each good (in the supplied by:</li> <li>Producer's certificate of analysis per each good (in the supplied by:</li> <li>Producer's certificate (only with first de Shipping document:</li> <li>Packing list</li> <li>ISO 9001 certificate (only with fir qualification)</li> <li>One of the documents must contair - Item name</li> </ul> </li> </ul>	stripes. 3 stripes per sid hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	de are necessary to ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>Ingots shall be stacked by stee avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to ma melting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the info - name of producer (name of smelte - name of goods (Mg metal)</li> <li>net weight (in KGs)</li> <li>serial number of the pallet (accord</li> <li>4.5. Delivery</li> <li>Pallets to be delivered by normal</li> <li>5. Accompanying documents:</li> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis per Safety Data Sheet: only with first de Shipping document</li> <li>Packing list</li> <li>ISO 9001 certificate (only with fir qualification)</li> <li>One of the documents must contain - Item name</li> </ul>	hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>avoid the lot falling apart.</li> <li>Foil sack as covering material s be placed under the sack to ma melting.</li> <li>Application of textile hoods is ne from damages during transport plastic stripes per each side.</li> <li>4.4. Marking (on two sides, giving the information of producer (name of smelter aname of goods (Mg metal))</li> <li>net weight (in KGs)</li> <li>serial number of the pallet (accord the series of the pallet stripes per each side)</li> <li>5. Accompanying documents:</li> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis per each given of the pallet for the pallet of the pallet is the series of the pallet for the pallet of the pallet is the supplied by:</li> <li>Producer's certificate of analysis per each given of the pallet of</li></ul>	hould be applied with eac ke the foil possible to be cessary with each lot to p tion. This textile hood sl	ch lot. Stripes should e moved before pre- protect the foil cover
<ul> <li>name of goods (Mg metal) <ul> <li>net weight (in KGs)</li> <li>serial number of the pallet (accord</li> </ul> </li> <li>4.5. Delivery <ul> <li>Pallets to be delivered by normal</li> </ul> </li> <li>5. Accompanying documents: <ul> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis performed to the supplied by:</li> <li>Safety Data Sheet: only with first definition of the documents must contain qualification)</li> <li>One of the documents must contain - Item name</li> </ul> </li> </ul>		
<ul> <li>Each delivery should be supplied by:</li> <li>Producer's certificate of analysis period safety Data Sheet: only with first deleters only with first deleters of the shipping document</li> <li>Shipping document</li> <li>Packing list</li> <li>ISO 9001 certificate (only with first qualification)</li> <li>One of the documents must contain - Item name</li> </ul>	10	lloaded from the side.
<ul> <li>Shipping document</li> <li>Packing list</li> <li>ISO 9001 certificate (only with fi qualification)</li> <li>One of the documents must contair</li> <li>Item name</li> </ul>	0	
<ul> <li>One of the documents must contain</li> <li>Item name</li> </ul>		
	:	
<ul> <li>Origin of the material</li> <li>Specification I.D. No. and th</li> <li>Purchase order number</li> <li>Name of the producer</li> </ul>	e modification date	
- Statement, which confirm by is free of radioactive contam		elivered to Arconic-Köfém

N	IATERIAL SPECIFICATION	
Arconic-Köfém Mill Products Hungary Llc.		
I.D. No.:	Magnesium	$\wedge$
O-SPEC-52-EURAMG100ING	SPECIFICATION	$\otimes$
Date: 2003.02.19.		ARCONIC
Modification: 8/07.11.2023		
Prepared by: Berki Csaba	Approved by: Szántó Ró	bert
Checked by: Szalai Viktor		

### 6. Other informations:

ARCONIC-KÖFÉM MILL PRODUCTS HUNGARY Llc. Casthouse maintains a quality management system as per AS9100D aerospace requirements.

Section 8.4.3. of AS9100D Standard requires you, suppliers of Arconic-Kofem Mill Products Hungary Llc. to meet certain notification/information requirements, with special attention to the following:

- Obligation to provide information if you become aware of a deviation that occurred in your process earlier and could adversely affect the product quality or production processes of Arconic-Kofem Mill Products Hungary Llc.
- Should you be forced to deliver product deviating from the product specification then a deviation permit shall be obtained from Arconic-Kofem Mill Products Hungary Llc. prior to the receipt of the shipment
- Arconic-Kofem Mill Products Hungary Llc. shall be notified on changes of the manufacture process or product quality, relocation of the production to another manufacturing plant.

Arconic-Kofém Mill Products Hungary Llc. requires from its suppliers/vendors that Arconic-Kofem Mill Products Hungary Llc. representatives and its customers will have the right to perform process audit or regulatory authority audit in the supplier's/vendor's plant or at the place of manufacturing at all reasonable times, upon advance notice. The supplier shall ensure the access to manufacturing areas and relevant records/documents for the purpose of the audit.

MATERIAL SPECIFICATION			
Arconic-Köfém Mill Products Hungary Llc.			
I.D. No.:	Magnesium	$\wedge$	
O-SPEC-52-EURAMG100ING	SPECIFICATION		
Date: 2003.02.19.		ARCONIC	
Modification: 8/07.11.2023			
Prepared by: Berki Csaba	Approved by: Szántó Ró	bert	
Checked by: Szalai Viktor			

Revision	Reason for Change	Changed Page(s)	Date of Change
6	Company name change. Chapter: 2. Fe and Mn level 4.4 pallets marking on two sides 5. Added to Accompanying documents: Purchase order number and name of the producer. SDS requirement 6. AS9100D	1, 2 and 3	11/03/2019
7	Company name change	1, 2 and 3 2	25/03/2019
8	Accompanying documents has been amended	2	07/11/2023